






# Fingerprint 2-in-1 Access Time Attendance System

FINGERIEC. AC900 series Fingerprint Access Control System delivers confidence and convenience by personalization of users through their fingerprints and eliminating the use of card system for door access. The FINGERIEC. AC900 series provides the perfect balance between stylish ultra-modern door access reader and its practicality. Deploying the world renowned university's fingerprint algorithm in its minutiae matching technique, the FINGERIEC. AC900 series ensures to provide access to only authorized people based on their enrolled fingerprint templates stored in the system. With the FINGERIEC. AC900 series, there is no more worries of unwanted intruders into your organization or misuse of cards and keys by irresponsible people.

The FINGERTEC. AC900 series is a user-friendly, reliable and flexible fingerprint authentication system that is capable of integration with other security solutions to ensure high-level protection that your premise requires. The FINGERTEC. AC900 series is a hassle-free model which makes set-up quick and easy with no more high wire, intensive labor, expensive equipments and high maintenance cost.

The FING@RTEC® AC900 series Fingerprint Access Control System is the ultimate door access system of today for your protected tomorrow!



One finge



# [ FEATURES & BENEFITS ]

- One-to-Many (1:N) Identification and One-to-One (1:1) Verification
- Allow a maximum of 10 fingerprints enrollment per user
- Allow rotation of fingerprint placement
- Possess storage capacity of 50,000 transactions
- Offer easy enrollment and fast clocking system
- All-in-one reader, no external controller needed
- PRS232, RS485, Ethernet, Wiegand 26-bits communication interface
- Easy-to-use management software
- Complete with buzzer feature
- Automatic activation of alarm in the event of break in, door ajar and illegal dismantle of reader.











## [ LAYOUT PLAN ]

### System Communication



## Natallation Diagram



	[ SPECIFICATIONS ]
Size (mm)	89 (L) x 188(H) x 36 (W)
Identification Time (s)	≤ 2 seconds
Enrollment	Up to 10 fingerprints per user
Fingerprint Placement	Any angle (360°)
FAR	< 0.0001%
FRR	< 1%
Transaction Storage	50,000
User Capacity	1,500 templates
Time Zone	50
Ethernet	10 / 100 BaseT (UDP)
Serial Communication (bps)	9600 / 19200 / 38400 / 57600 / 115200 (RS232) 38400 (RS485)
Wiegand	26-bits
Operating Temperature (°C)	0 - 45
Operating Humidity (%)	20 - 80
Operating Voltage	DC 12V 3A
EM-Lock Driving Output	DC 12V 3A
Display Language	English, Chinese



www.fingertecindia.com

Call: 079-26574943, 40068968 sales@payrollsoftware.co.in

